

HTY511DAUS

Family	Dishwasher
Subfamily	Hoodtype dishwasher
Basket dimensions	500x500 mm
Power connection	400 V 3N~ / 16 A / 9,7 kW / 50 Hz
Width	620 mm
Depth	736 mm
Height	1530 mm
Usable load height	440 mm



Distribution

Solutions	Bars/Cafes; Hotels; Restaurants/Catering; Butcher's shops; Schools; QSR
-----------	--

Aesthetics

Serie	Easyline	Led color	Red
Control panel	Electronic		

Functions



Functionality	GN 1/1 trays washing; Triple filter; SHR+; HTR; Door clearance 440mm
---------------	--

Programs

Programs		
Boiler 85°C/Tank 60°C-1'30"	Boiler 85°C/Tank 60°C-2'30"	Boiler 85°C/Tank 60°C-4'
Drain and self cleaning cycle	Yes	
Maximum basket/hour	40	
Maximum dishes/hour	720	

Interface

Panel	Ecoline 2016	On/Off button	Yes
Display	4 digit	Manual diagnostic	Yes
Number of buttons	5		

Construction

Tank	Deep drawn	Hood	Double wall
Tank construction	Double wall	Tank capacity	14 l
Tank material	Stainless steel AISI 304	Boiler capacity	8 l
Back panel	Prepainted	Rumorosità	Lpa 59,9 dBA
Tank filter	Stainless steel	Protection class	IPX4
Washing spray arm	Stainless steel	Net weight	115.000 kg
Rinse spray arm	Stainless steel	Drain max. height	1000 mm

Consumption and connections

Tank heating element	2200 W	Water cycle consumption	2,7 l
Boiler heating element	9000 W	Water inlet	Cold 15°C
Washing pump	700 W	Max temperature inlet water	60°C
Default connection	9700 W	Max water hardness	12°FH - 7°dH
Electrical connection option	230 V~ / 29 A / 6,7 kW / 50 Hz; 400 V 3N~ / 13 A / 6,7 kW / 50 Hz	Water inlet	Cold 15°C

Manuals and Certifications

Certificate	CE, Watermark
-------------	---------------

Equipments

Peristaltic detergent doser	Yes, electronic control	Default chemicals dosing unit of measure	gr/lt
Peristaltic detergent doser	Yes, manual	Drain pump with 3 stage filter system	Yes
Peristaltic rinse-aid doser	Yes, electronic control	Rinse pump H.T.R. system	Rinse pump with atmospheric boiler
Detergent load	Yes, manual	Break tank	Yes
Peristaltic detergent doser	Yes, manual	Partial renewal of water in the tank and built-in drain pump	Si
Rinse load	Yes, manual	Water supply pipe diameter	16 mm
Soft Start	Yes	Drain supply pipe diameter	21,5 mm
Boiler thermostop	Yes default ON	Automatic start	Yes, default OFF
Cycle counter	Yes		

Trays washing option Yes
GN1/1 530x325mm

Accessories Included

Dish basket PB50D01
Cutlery basket PHOOS02
Flat basket 1x PB50G02

Water supply pipe In acciaio Watermark
Drain pipe Yes - 2m

Not included accessories



WH00S01

Wire insert for 12 small dishes




PHOOS01

Single basket in polypropylene for cutlery



WB50G01

Universal wire basket with flat bottom
500x500



PB50D01

Basket made of polypropylene for 18
plates 500x500



WB50G02

Wire basket for glasses with inclined
bottom 500x500



WB50G04

Wire basket for glasses with inclined
bottom 500x500



PHOOS02

Basket in polypropylene for cutlery with
6 compartments



WB50D01

Wire basket for 18 dishes and trays
500x500



WB50G03

Wire basket for glasses with inclined
bottom 500x500

Symbols glossary (TT)

